productinformation

tesa® 62852

Double-sided PE foam tape

tesa® 62852 is a double-sided tape consisting of a PE foam backing and a pure acrylic adhesive.

tesa® 62852 features especially:

- High ultimate adhesive strength for a secure bonding performance
- Conformable foam backing to compensate design tolerances or uneven surfaces
- Excellent temperature resistance performance
- Excellent converting properties

Main Application

Permanent mounting of emblems and letters; e.g. single letters for classification of car model or engine data

Technical Data

Backing material	PE foam	Tensile strength	8 N/cm
Color	black	Type of liner	glassine
Total thickness	510 μm	Colour of liner	brown
Type of adhesive	pure acrylic	Thickness of liner	71 μm
Elongation at break	400 %	Weight of liner	80 g/m ²

Adhesion to

Steel (initial)	9.5 N/cm	Steel (after 14 days)	20.0 N/cm
ABS (initial)	6.0 N/cm	ABS (after 14 days)	13.0 N/cm
PE (initial)	1.5 N/cm	PE (after 14 days)	1.5 N/cm

Properties

•	Static shear resistance at 23°C	•••			
•	Temperature resistance long term	90 °C	•	Static shear resistance at 70°C	••••
•	Temperature resistance short term	100 °C	•	Static shear resistance at 40°C	••••

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low